

PRODUCT DESCRIPTION

Oscar Jade 2T is a lubricant for 2-Stroke scooter engines with premix or injector lube system, operating at high rpm. Reinforced with synthetic base stocks for outstanding oil film resistance and anti-wear protection. Minimizes smoke and deposits.

APPLICATION

For use in motorcycles, snowmobiles and lean oil/fuel ratio chain saws.

PROPERTIES

- Good wear protection
- Thermal and oxidation stability and deposit control
- Reduces pre-ignition
- Good corrosion protection properties

PERFORMANCE LEVELS

Meets and exceeds:

- API TC; JASO FC

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	OSCAR JADE 2T
Viscosity Grade			30
Density @ 15°C, kg/l	ASTM D1298	kg/l	0.859
Viscosity @ 100°C, cSt	ASTM D445	cSt	8.8
Viscosity @ 40°C, cSt	ASTM D445	cSt	53.8
Viscosity Index (min)	ASTM D2270	-	140
Pour Point, °C	ASTM D97	°C	-39
Flash Point, °C	ASTM D92	°C	245
Total Base Number (TBN), m KOH/g	ASTM D2896	m KOH/g	1.5

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.oscarlubricants.com