

PRODUCT DESCRIPTION

Oscar Jade 4T Endurance is a 100% synthetic 4-Stroke lubricant. Excellent shear resistance protecting engine and gearbox. Smooth shifting. Meets JASO MA2 specifications for optimal wet clutch performance.

APPLICATION

Meets bike manufacturer specifications, especially HUSQVARNA, KTM and MOTO GUZZI which recommend SAE 10W60. Suitable for catalytic converters. Specifically designed for powerful high performance bikes, sports bikes, street & road bikes, trails, off road bikes fitted with 4 stroke engines, any engine displacement, with or without catalytic converters, with integrated gearbox and wet clutch.

PROPERTIES

- Reduces engine internal friction
- Improves mechanical efficiency
- Very low volatility to reduce oil consumption
- Anti-oxidation, Anti-corrosion, Anti-foam properties

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	OSCAR JADE 4T ENDURANCE
Viscosity Grade			10W60
Density @ 15°C, kg/l	ASTM D1298	kg/l	0.860
Viscosity @ 100°C, cSt	ASTM D445	cSt	24.0
Viscosity @ 40°C, cSt	ASTM D445	cSt	156
Viscosity Index (min)	ASTM D2270	-	185
Pour Point, °C	ASTM D97	°C	-33
Flash Point, °C	ASTM D92	°C	236
Total Base Number (TBN), m KOH/g	ASTM D2896	m KOH/g	8.0

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.oscarlubricants.com