

PRODUCT DESCRIPTION

Oscar 4T Eco Scooter is a mineral motorcycle oil specially designed to meet today's 4-Stroke scooter specifications where a 20W40/50 viscosity grade and the JASO MB specification are required. JASO MB lubricant ensures optimal engine performance and fuel economy on all scooters without wet clutch.

APPLICATION

For older scooters without wet clutch and where JASO MB specification is required.

PROPERTIES

- Reduces oil consumption
- Provides Low Emission
- Outstanding detergent and anti-wear properties

PERFORMANCE LEVELS

Meets and exceeds:

- API SG; JASO MB

TYPICAL PROPERTIES

| PARAMETERS | TEST METHOD | UNIT | OSCAR JADE 4T ECO SCOOTER | |
|----------------------------------|-------------|---------|---------------------------|-------|
| Viscosity Grade | | | 20W40 | 20W50 |
| Density @ 15°C, kg/l | ASTM D1298 | kg/l | 0.880 | 0.880 |
| Viscosity @ 100°C, cSt | ASTM D445 | cSt | 15.0 | 18.5 |
| Viscosity @ 40°C, cSt | ASTM D445 | cSt | 122 | 160 |
| Viscosity Index (min) | ASTM D2270 | - | 126 | 126 |
| Pour Point, °C | ASTM D97 | °C | -25 | -25 |
| Flash Point, °C | ASTM D92 | °C | 230 | 230 |
| Total Base Number (TBN), m KOH/g | ASTM D2896 | m KOH/g | 7.0 | 7.0 |

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.oscarlubricants.com