PRODUCT DATA SHEET

Oscar Chainsaw Oil 100

DESCRIPTION

Oscar Chainsaw Oil 100 is a mineral-based high-performance oil for once-through loss lubrication. Thanks to the outstanding adhesion properties and first-class lubricating effect, provides optimum protection of moving parts such as chain links and joints against wear and corrosion.

PROPERTIES

This lubricant assures:

- outstanding lubricating action
- outstandingly adherent
- excellent low temperature behavior
- excellent viscosity/temperature properties

APPLICATIONS

The specifications and instructions from the assembly or equipment manufacturer must be followed.

Meets the requirements of: API SJ

TYPICAL PROPERTIES

Oscar Chainsaw Oil 100		
Typical Properties	**ISO Grade**	**100**
	Performance	**N/A**
Test Parameters	**ASTM Method**	**Typical Values**
Density @ 15˚C, kg/l	ASTM D1298	0.87
Viscosity @ 100˚C, cSt	ASTM D445	13
Viscosity @ 40˚C, cSt	ASTM D445	100
Viscosity Index	ASTM D2270	128
Flash Point, ˚C	ASTM D92	220
Pour Point , ˚C	ASTM D97	-35

August 2020

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice.