PRODUCT DATA SHEET

Oscar AgriSYN™ UTTO

DESCRIPTION

Oscar AgriSYN UTTO is a super high-performance fully synthetic multifunctional transmission lubricant for construction machinery.

PROPERTIES

This lubricant assures:

- highest pressure-absorption capability
- wear reduction
- noise reduction
- excellent viscosity/temperature properties
- excellent ageing resistance
- all sealing materials compatibility

APPLICATIONS

Specially developed for very heavily loaded hydraulic and transmission systems of agricultural and earthmoving machines.

Meets the requirements of: API GL-4; Allison C4; Case MS1207/MS1209; Cat TO-2; John Deere J20A; Massey; Ferguson M1141/M1143/M1145; Volvo WB 102; ZF TE-ML 03E

TYPICAL PROPERTIES

Oscar AgriSYN UTTO		
Typical Properties	**SAE Grade**	**N/A**
	Performance	**GL-4**
Test Parameters	**ASTM Method**	**Typical Values**
Density @ 15˚C, kg/l	ASTM D1298	0.86
Viscosity @ 100˚C, cSt	ASTM D445	7.6
Viscosity @ 40˚C, cSt	ASTM D445	39
Viscosity Index	ASTM D2270	160
Flash Point, ˚C	ASTM D92	230
Pour Point , ˚C	ASTM D97	-35

August 2020

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice.