

Oscar OEM Specific F SAE 5W30 is a very high performance, low viscosity fluid, fully synthetic mainline lubricant for gasoline and light vehicle diesel engines, including the ones complying with ACEA A5/B5 standard. These oils may be unsuitable for use in some engines. Helps to lengthen the engine life thanks to its excellent resistance to temperature variations and permits an extralong oil change interval.

APPLICATION

Gasoline and diesel engines of passenger cars. These oils may be unsuitable for use in some engines.

PROPERTIES

- Fuel Economy
- Long Drain Capability in Europe

PERFORMANCE LEVELS

Meets and exceeds: ACEA A5/B5, Ford WSS-M2C913-D; Ford WSS-M2C913-C; Renault RN 0700

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	OSCAR OEM SPECIFIC F
Viscosity Grade			5W30
Density @ 15°C	ASTM D1298	kg/l	0.850
Viscosity @ 100°C	ASTM D445	cSt	10
Viscosity @ 40°C	ASTM D445	cSt	52
Viscosity Index (min)	ASTM D2270	-	160 min
Cold Crank Simulator	ASTM D5293	cP	5,800 @ -30 °C
HTHS Viscosity 150°C	-	mPa.s	≥ 2.9 and ≥ 3.5
Pour Point	ASTM D97	°C	-40
Flash Point	ASTM D92	°C	Min. 230
Total Base Number (TBN)	ASTM D2896	mg KOH/g	11

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.oscarlubricants.com