

# PRODUCT DATA SHEET

## Oscar STOU 10W30/15W30



### DESCRIPTION

---

**Oscar STOU** is a synthetic blend, extra high performance, multi-functional lubricant for most farm equipment applications

### PROPERTIES

---

This lubricant assures:

- Reduced sludge build-up and high temperature deposits
- wear reduction
- noise reduction
- TBN reserves
- Effective detergency/dispersancy
- excellent ageing resistance
- Longer gasket and seal life

### APPLICATIONS

---

Mixed diesel and gasoline-powered farm vehicles engines, transmissions and power systems requiring multifunctional fluid.

Meets the requirements of: API CF/GL 4, Caterpillar TO-2; John Deere J27, J20CI Ford's Super Tractor Oil Universal (STOU) applications (M2C 159B); Massey-Ferguson CMS 1135 and CMS 1139; Allison C-4

### TYPICAL PROPERTIES

---

Oscar UTTO			
Typical Properties	SAE Grade	15W30	10W30
	Performance	CF/GL-4	CF/GL-4
Test Parameters	ASTM Method	Typical Values	Typical Values
Density @ 15°C, kg/l	ASTM D1298	0.885	0.870
Viscosity @ 100°C, cSt	ASTM D445	10.90	10.50
Viscosity @ 40°C, cSt	ASTM D445	65.6	69
Viscosity Index	ASTM D2270	140	135
Flash Point, °C	ASTM D92	220	230
Pour Point, °C	ASTM D97	-25	-30

*The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice.*

October 2023