

## Oscar HydraXP 10W

### PRODUCT DESCRIPTION

**Oscar HydraXP 10W** is a high-performance hydraulic oil formulated from advanced base oils and a balanced additive system designed to satisfy a wide range of heavy-duty hydraulic equipment requirements

### APPLICATION

- Hydraulic systems and components used in conjunction with equipment from leading American, European, and Japanese manufacturers.
- Hydraulic systems where wide ambient temperatures are encountered

### PROPERTIES

This lubricant assures delivers excellent performance in a wide range of hydraulic systems and components using various multi-metal designs. The product also provides effective low and high ambient temperature performance due to high viscosity index. Its' excellent oxidation resistance delivers good performance at higher temperatures and extended operating intervals.

### TYPICAL PROPERTIES

Oscar HydraXP 10W		
Typical Properties	SAE Grade	10W
	API level	N/A
Test Parameters	ASTM Method	Typical Values
Density @ 15°C, kg/l	ASTM D1298	0.876
Viscosity @ 100°C, cSt	ASTM D445	5.89
Viscosity @ 40°C, cSt	ASTM D445	37.9
Viscosity Index	ASTM D2270	96
Flash Point, °C	ASTM D92	232
Pour Point, °C	ASTM D97	-30

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.oscarlubricants.com](http://www.oscarlubricants.com)