

Oscar HDM UTTO 10W30 WB 101

PRODUCT DESCRIPTION

Oscar HDM UTTO 10W30 WB 101 is a super high-performance multifunctional transmission lubricant for construction machinery.

APPLICATION

Used in powered transmission and axle drives, especially for high-load hypoid gearings. Not to be used as engine oil.

PROPERTIES

This lubricant assures:

- highest pressure-absorption capability
- wear reduction
- noise reduction
- excellent viscosity/temperature properties
- excellent ageing resistance
- all sealing materials compatibility

PERFORMANCE LEVEL

Meets the requirements of: API GL 4, Case New Holland MAT-3525, M2C-134 A-D, FNHA-2- D.201.00, John Deere JDM-J20C, Massey-Ferguson M1143, M1145, Volvo WB 101, Transmission Oil 97303:015, ZF TE-ML 03E, 05F, 06D, 06K, 06M, 06N, 06R, 17E, 21F, Caterpillar TO-4

TYPICAL PROPERTIES

Oscar HDM UTTO		
Typical Properties	SAE Grade	10W30
	Performance	GL-4
Test Parameters	ASTM Method	Typical Values
Density @ 15°C, kg/l	ASTM D1298	0.870
Viscosity @ 100°C, cSt	ASTM D445	10.50
Viscosity @ 40°C, cSt	ASTM D445	69
Viscosity Index	ASTM D2270	135
Flash Point, °C	ASTM D92	230
Pour Point, °C	ASTM D97	-25

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.oscarlubricants.com