

PRODUCT DESCRIPTION

Oscar CoolCar Long Life Antifreeze Coolant G12 50% is a ready to use automotive radiator fluid composed of demineralized water, ethylene glycol and an advanced blend of balanced corrosion inhibitors based on OAT technology. It's designed to protect the cooling systems of water-cooled petrol engines.

APPLICATION

The majority of passenger cars' and light diesel vehicles' radiators can use Oscar CoolCar G12 Coolant. Oscar CoolCar is a full mono ethylene glycol-based coolant for a liquid cooled crankcase system. It contains anti-corrosion and anti-rust additives based on OAT technology. It is harmless to rubber and does not foam or clog radiators.

PERFORMANCE LEVELS

Meets and exceeds:

VW/Audi/Seat/Porsche, VW G12; MB 325.3; MAN 324 Type SNF; ASTM D 3306; ASTM D 4656; ASTM D 4985; ASTM D 5345; SAE J814C; SAE J1038; SAE J1941; SAE J1034; Ford WSS M97 B44-D

TYPICAL PROPERTIES

PARAMETERS	UNIT	Oscar CoolCar G12 50%
pH	-	8.5
Freezing Point	°C	-36
Density @ 15°C	kg/l	1.07
Boiling point	°C	109

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.oscarlubricants.com