



United States Accreditation Council

7950 NW, 53rd Street, Suite 337, Miami, Florida 33166 USA

Website: www.usacamerica.us

ANNEXURE TO 17025 CERTIFICATE NO. 18189

Date: 18/02/2026

Company Name: - Oscar Lubricants LLC

Manufacturer: Building 21, Street 85, New Industrial Area 2, Ajman, United Arab Emirates

Certificate No.:- 18189 (Valid until: **15/02/2029**)

ID. No.	Equipment Name	Manufacturer	Model	Serial No.
KTL-XRF-19	ED-XRF	Ametek Materials Analysis	Spectro Xpeos	76004852
KTL-VIS-01	Kinematic Viscosity Tester (100 °C+ 40 °C)	Dalian All World I/EC Co. Ltd.	AWD-03	MCR7003-A, B
KTL-VIS-03	Viscometer, Density and VI	Anton Paar	SVM 3100	
KTL-PP-04/1	Mini Pour/Cloud Point Tester (PP)	TANAKA	MPC-102S	74940
KTL-FP-08	Cleveland Open Cup Flash Point Tester	Parisam Technology	PT-1015 M	PT-02361389
KTL-FM-11	Foaming M/C	DOTT. GIANNI SCAVINI	AD0892_200	101494-TC-01,02
KTL-NCK-57	SELBY-NOAC Volatility Tester	TANNAS	NA	1503-069
KTL-CCB-16	Copper Corrosion Bath	WADE6ATILABEQUIP		D-06115
KTL-FIR-17	FT IR	Bruker	Alpha	102911
KTL-CCS-21/2	CCS Circulating Bath	JULABO	FE 500	10109692
KTL-TB-28	Turbidity Meter	HACH	2100AN	040-RM 170
KTL-FM-13	Foaming M/C For Coolant	Tamson Instrument	D892FOAM	24T157-TC-01



United States Accreditation Council

7950 NW, 53rd Street, Suite 337, Miami, Florida 33166 USA

Website: www.usacamerica.us

Parameters	Method
Appearance	Visual
Color	ASTM D1500
Odor	NA
Turbidity, N.T.U.	NA
Viscosity @ 100°C, cSt	ASTM D445
Viscosity @ 40°C, cSt	ASTM D445
Viscosity Index	ASTM D2270
Pour point, °C	ASTM D6749
Density @ 15°C	ASTM D1298
Flash Point (COC), °C	ASTM D92
Total Base Number, mg KOH/g	ASTM D2896
CCS @ -15°C, mPa-s	ASTM D5293
Foaming Test	ASTM D892
Total Acid Number, mg KOH/g	ASTM D664
Sulphated Ash, %wt.	ASTM D874
NOACK Volatility, %	ASTM D5800
Barium, %wt.	ASTM D6481
Calcium, %wt.	ASTM D6481
Magnesium, %wt.	ASTM D6481
Molybdenum, %wt.	ASTM D6481
Phosphorus, %wt.	ASTM D6481
Sodium, %wt.	ASTM D6481
Sulfur, %wt.	ASTM D6481
Zinc, %wt.	ASTM D6481
Zirconium, %wt.	ASTM D6481
Nitrogen, %wt.	ASTM D5291
Water Separability(37-43-0) ml. minutes	ASTM 1401
Water Content, ppm	ASTM D6304
Shear Stability Index	ASTM D6278
Sediment, %wt.	ASTM D2273
Cu Corr.Test 121 Deg.C 3 Hours GL5 () %wt.	ASTM D130
Cu Corr.Test 121 Deg.C 3 Hours GL4 () %wt.	ASTM D130
Cu Corr.Test 100 Deg.C 3 Hours Ind () %wt.	ASTM D130
RPVOT, minutes	ASTM D2272
Fourrier Transformer Infrared (FTIR)	NA